

13 Wall & Ceiling LED>Outdoor Slim Range Up & down beam

67412/AN/W



2x6W LED wall light with adjustable beam, ideal for both indoor and outdoor installation.

Complete with 500mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|--------------|-----------------------------------|
| Item Group | 13 Wall & Ceiling LED |
| Family | Outdoor Slim Range Up & down beam |
| Order Code | 67412/AN/W |
| Colour | Anthracite |
| Material | Die Cast |
| Shape | Rectangular |
| Length | 180mm |
| Width | 42mm |
| Height | 115mm |
| Surface Wall | Yes |
| Indoor | Yes |
| Outdoor | Yes |

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

2x6W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

500mA

Voltage

10V

Safety Class



Power(Watts)

5W

IP Rating

IP54

Light Source

LED built in

LED Type

COB

LED Brand

Edison

F Mark



Gear

Gear Type


Led Driver

Input Voltage

220-240V

| | |
|------------------|---|
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 6-12W |
| Power Factor | 0,5 |
| Constant Current | Yes |
| 500mA | 12-24V |
| IP Rating | IP20 |
| Safety Class |  |
| Brand | Eaglerise |
| Protection | 0 |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 2x400lm |
| Light Efficiency | 66,67lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Weight | 0.933kg |
| Pcs/Carton | 12 |
| Barcode | 5291889056362 |
| HS Code | 9405409900 |

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

