

Product Datasheet

www.1-light.eu

13 Wall & Ceiling LED>Outdoor Slim Range Up & down beam

67412/W/W



2x6W LED wall light with adjustable beam, ideal for both indoor and outdoor installation.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads







Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Outdoor Slim Range Up & down beam
Order Code	67412/W/W
Colour	White
Material	Die Cast
Shape	Rectangular
Length	180mm
Width	42mm
Height	115mm
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x6W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Type Input Current	Constant Current 500mA
Input Current	500mA
Input Current Voltage	500mA 10V
Input Current Voltage Safety Class	500mA 10V
Input Current Voltage Safety Class Power(Watts)	500mA 10V (III) 5W
Input Current Voltage Safety Class Power(Watts) IP Rating	500mA 10V
Input Current Voltage Safety Class Power(Watts) IP Rating Light Source	500mA 10V III 5W IP54 LED built in
Input Current Voltage Safety Class Power(Watts) IP Rating Light Source LED Type	500mA 10V III 5W IP54 LED built in COB
Input Current Voltage Safety Class Power(Watts) IP Rating Light Source LED Type LED Brand	500mA 10V 11I 5W IP54 LED built in COB Cree
Input Current Voltage Safety Class Power(Watts) IP Rating Light Source LED Type LED Brand	500mA 10V 11I 5W IP54 LED built in COB Cree
Input Current Voltage Safety Class Power(Watts) IP Rating Light Source LED Type LED Brand F Mark	500mA 10V 11I 5W IP54 LED built in COB Cree

Colour Temperature Lumen Output Light Efficiency CRI Box Weight Box Weight 3000K 2x400Im 66,67Im/W 66,67Im/W 80	50 Hz	Yes	Pobrano z mamadecor.pl
Power Factor Constant Current Yes 500mA 12-24V IP Raling P20 Safety Class Brand Eaglerise Protection O Colour Temperature Lumen Output Light Efficiency CRI Saking Info Box Weight O D,5 Yes 12-24V 12-	60 Hz	Yes	
Constant Current 500mA 12-24V IP Rating IP20 Safety Class Brand Eaglerise Protection Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Box Weight Down A 12-24V 12-	Power(Watts)	6-12W	
12-24V 1	Power Factor	0,5	
IP Rating Safety Class Brand Brand Protection Colour Temperature Lumen Output Light Efficiency CRI Blumination Diagram Box Weight Box Weight IP20 Eaglerise Baglerise Ba	Constant Current	Yes	
Safety Class Brand Eaglerise Protection Colour Temperature Lumen Output Light Efficiency CRI Blumination Diagram Exclusion Diagram Exclusion Info Box Weight Diagram D	500mA	12-24V	
Brand Eaglerise Protection Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Box Weight Diagram Eacking Info Eaglerise Again and a separation of the separation o	IP Rating	IP20	
Protection 0 Colour Temperature 3000K Lumen Output 2x400lm Light Efficiency 66,67lm/W CRI 80 Illumination Diagram Colour Temperature 2x400lm Light Efficiency 80 Light Efficiency 80	Safety Class		
Lumination Data Colour Temperature Lumen Output Light Efficiency CRI Bullimination Diagram Box Weight Box Weight Solution Data 3000K 2x400Im 66,67Im/W 66,67Im/W 80 90 90 90 90 90 90 90 90 90	Brand	Eaglerise	
Colour Temperature Lumen Output Light Efficiency CRI Box Weight Box Weight 3000K 2x400Im 66,67Im/W 66,67Im/W 80	Protection	0	
Colour Temperature Lumen Output Light Efficiency CRI Box Weight Box Weight 3000K 2x400Im 66,67Im/W 66,67Im/W 80			
Lumen Output Light Efficiency CRI Illumination Diagram Racking Info Box Weight 2x400Im 66,67Im/W 80	Illumination Data		
Lumen Output Light Efficiency CRI Illumination Diagram Racking Info Box Weight 2x400Im 66,67Im/W 80			
Light Efficiency CRI Box Weight 66,67Im/W 80 CRI CRI 80 CRI CRI CRI CRI CRI CRI CRI CR	Colour Temperature	3000K	
CRI Illumination Diagram Packing Info Box Weight 0.933kg	Lumen Output	2x400lm	
Box Weight 0.933kg	Light Efficiency	66,67lm/W	
Packing Info Box Weight 0.933kg	CRI	80	
Box Weight 0.933kg	Illumination Diagram		
Box Weight 0.933kg			
Box Weight 0.933kg	Packing Info		
Dec/Conton	Box Weight	0.933kg	
PCS/Carton 1/2	Pcs/Carton	12	
Barcode 5291889056355	Barcode	5291889056355	
HS Code 9405409900	HS Code	9405409900	

Yes

switch to one light!

Weee Directive

