

## 13 Wall &amp; Ceiling LED &gt; Outdoor Wall Lights

## 67492P/AN/W



12W LED Wall light with movement sensor.

Working time-delay: 5s, 30s, 1Min, 3 Min, 5 Min, 8 Min.

Ambient light : Distance: 8m

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Outdoor Wall Lights
Order Code	67492P/AN/W
Colour	Anthracite
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	170mm
Width	140mm
Height	170mm
Surface Wall	Yes
Indoor	Yes

## Electrical Characteristics

## Gear

Built In

## Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

12W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



## Fitting

Input Type

Constant Current

Input Current

300mA

Voltage

38V

Power(Watts)

11,6W

IP Rating

IP54

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

## Gear

Gear Type

Led Driver

Input Voltage


220-240V

50 Hz


Yes

60 Hz

Yes

Power(Watts)	6-12W
Power Factor	0,5
Constant Current	Yes
300mA	20-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise

### Illumination Data

Colour Temperature	3000K
Lumen Output	600lm
Light Efficiency	50lm/W
CRI	80
Illumination Diagram	

### Packing Info

Box Weight	0.875kg
Pcs/Carton	12
Barcode	5291889066187
HS Code	9405114090

Warranty

2 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

