

20 Garden &amp; Underwater&gt;The Project Bollard Range

67510A/AN/C



20W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Accessories



050210/AN

## Physical Specification

Item Group

20 Garden &amp; Underwater

Family

The Project Bollard Range

Order Code

67510A/AN/C

Colour

Anthracite

Material



Die Cast

Shape

Circular


Height	600mm
Diameter	160mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	10

## Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	32,8V
Power(Watts)	16,4W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Edison

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	15-21W
Power Factor	0,9
Constant Current	Yes
500mA	30-42v
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Brand	HEP
Protection	Short Circuit

## Illumination Data

Colour Temperature	4000K
Lumen Output	2000lm
Light Efficiency	100lm/W
CRI	80
Illumination Diagram	

## Packing Info

Box Weight	4.850kg
Pcs/Carton	2
Barcode	5291889069072

Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

