

## 13 Wall & Ceiling LED>COB Outdoor Ceiling Cylinders

## 67516C/W/W



40W COB LED cylinder, IP65, suitable for indoor and outdoor installation.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads





### Dimensions



### Physical Specification


Item Group	13 Wall & Ceiling LED
Family	COB Outdoor Ceiling Cylinders
Order Code	67516C/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	183mm
Diameter	160mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

## Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	34,17V
Power(Watts)	34,17W
IP Rating	IP65
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	27-40W
Power Factor	0,9

Constant Current	Yes
1000mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	KEGU

#### Illumination Data

Colour Temperature	3000K
Lumen Output	3200lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	40°
Illumination Diagram	
Dark Light	Yes

#### Packing Info

Box Length	9cm
Box Width	9cm
Box Height	16cm
Box Weight	2.266kg
Pcs/Carton	6
Barcode	5291889070115
HS Code	9405409900

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

