

Product Datasheet

www.1-light.eu

19 Wall Recessed & Inground>Outdoor Dark Light Wall Recessed Die cast

68066/AN/W



8,5W LED wall recessed light, IP65, ideal for both indoor and outdoor installation.

Complete with 500mA driver.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.













Downloads







Dimensions



Physical Specification

Item Group	19 Wall Recessed & Inground
Family	Outdoor Dark Light Wall Recessed Die cast
Order Code	68066/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	250mm
Width	87mm
Height	73mm
Cutout Hole Width	238mm
Cutout Hole Length	74mm
Recessed wall	Yes

Depth Required	80mm	Pobrano z mamadecor.pl
Indoor	Yes	
Outdoor	Yes	
Adjustable	No	
The strice I Characteristics		


Electrical Characteristics Gear Built In Fitting + Driver Input Voltage 100-240V Yes 50 Hz 60 Hz Yes Safety Class Power(Watts) 8,5W IP Rating IP65 LED built in Light Source Dimmable No F F Mark Fitting Input Type **Constant Current** Input Current 500mA Voltage 16V Safety Class Power(Watts) 8W IP Rating IP65 Light Source LED built in LED Type SMD LED Brand Philips LED Number 40



Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,25-9W
Power Factor	0,9
Constant Current	Yes
500mA	6,5-18V
IP Rating	IP20
Safety Class	
Manufacturer	HEP
Protection	0
Illumination Data	
	3000K
Colour Temperature Lumen Output	3000K 160lm
Colour Temperature	
Colour Temperature Lumen Output	160lm
Colour Temperature Lumen Output Light Efficiency	160lm 18,82lm/W
Colour Temperature Lumen Output Light Efficiency CRI	160lm 18,82lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	160lm 18,82lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	160lm 18,82lm/VV 80 44°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	160lm 18,82lm/VV 80 44°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info	18,82lm/W 80 44° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length	160lm 18,82lm/W 80 44° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length Box Width	160lm 18,82lm/W 80 44° Yes 11cm 10,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length	160lm 18,82lm/W 80 44° Yes

Pcs/Carton	12	Pobrano z mamadecor.pl
Barcode	5291889048190	
HS Code	9405409900	

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to one light!

