

Product Datasheet

www.1-light.eu

19 Wall Recessed & Inground>Outdoor Dark Light Wall Recessed Die cast

68068/AN/W



3W LED wall recessed light, IP65, ideal for both indoor and outdoor installation.

Complete 350mA driver.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.













Downloads









Dimensions




Physical Specification

Item Group	19 Wall Recessed & Inground
Family	Outdoor Dark Light Wall Recessed Die cast
Order Code	68068/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Circular
Height	35mm
Diameter	114mm
Cutout Hole Diameter	110mm Concrete 100mm Gypsum
Recessed wall	Yes
Depth Required	60mm
Indoor	Yes

Outdoor	Yes	Pobrano z mamadecor.pl
Adjustable	No	
lectrical Characteristics		
icotriodi Characteristico		
Gear	Built In	
Fitting + Driver		
Input Voltage	100-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	3W	
IP Rating	IP65	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	350mA	
Voltage	8V	
Safety Class	\(\overline{\text{III}}\)	
Power(Watts)	2,8W	
IP Rating	IP65	
Light Source	LED built in	
LED Type	SMD 2835	
LED Brand	Osram	
LED Number	6	
F Mark	F	
Gear		

Gear Type	Led Driver	Pobrano z mamadecor.pl
Input Voltage	100-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	1-4W	
Power Factor	0,5	
Constant Current	Yes	
350mA	3-10V	
IP Rating	IP20	
Safety Class		
Brand	Galoppato	
Protection	0	
Ilumination Data		
Colour Temperature	3000K	
Lumen Output	300lm	
Light Efficiency	100lm/W	
CRI	80	
Illumination Diagram		
Dark Light	Yes	
Packing Info		
Box Length	13cm	
Box Width	7,5cm	
Box Height	13cm	
Box Weight	0,4Kg	
Pcs/Carton	24	
Barcode	5291889049517	
HS Code	9405409900	



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to one light!

