
Product Datasheet

www.1-light.eu

19 Wall Recessed & Inground>Outdoor Dark Light Wall Recessed Die cast

68068A/AN/W



4W LED wall recessed light, IP65, ideal for both indoor and outdoor installation.

Complete 350mA driver.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.













Downloads










Dimensions



Physical Specification

Item Group	19 Wall Recessed & Inground
Family	Outdoor Dark Light Wall Recessed Die cast
Order Code	68068A/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	115mm
Width	115mm
Height	35mm
Cutout Hole Width	110mm
Cutout Hole Length	110mm
Recessed wall	Yes

Depth Required	60mm	Pobrano z mamadecor.pl
Indoor	Yes	
Outdoor	Yes	
Adjustable	No	
The strice I Characteristics		

Electrical Characteristics Gear Built In Fitting + Driver Input Voltage 100-240V Yes 50 Hz 60 Hz Yes Safety Class 4W Power(Watts) IP Rating IP65 Light Source LED built in Dimmable No F F Mark Fitting Input Type **Constant Current** Input Current 350mA Voltage 9V Safety Class Power(Watts) 3,15W IP Rating IP65 Light Source LED built in LED Type SMD 2835 LED Brand Osram LED Number 6




Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	1-4W
Power Factor	0,5
Constant Current	Yes
350mA	3-10V
IP Rating	IP20
Safety Class	
Brand	Galoppato
Protection	0
Illumination Data Colour Temperature	3000K
	3000K 300lm
Colour Temperature	
Colour Temperature Lumen Output	300lm
Colour Temperature Lumen Output Light Efficiency	300lm 100lm/W
Colour Temperature Lumen Output Light Efficiency CRI	300lm 100lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	300lm 100lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	300lm 100lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Dark Light	300lm 100lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Dark Light Packing Info	300lm 100lm/VV 80 Yes
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Dark Light Packing Info Box Length	300lm 100lm/W 80 Yes
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Dark Light Packing Info Box Length Box Width	300lm 100lm/W 80 Yes 13cm 7,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Dark Light Packing Info Box Length Box Width Box Height	300lm 100lm/W 80 Yes 13cm 7,5cm

9405409900

HS Code

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

