

Product Datasheet

www.1-light.eu

14 Plafo>The LED Plafo Outdoor Round

67280AN/W/W



24W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



Physical Specification

Item Group	14 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280AN/W/W
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	83mm
Diameter	300mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No	Pobrano z mamadecor.p
IK Rating	8	
ctrical Characteristics		
Gear	Built In	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	24W	
IP Rating	IP65	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	600mA	
Voltage	38V	
Power(Watts)	22,8W	
IP Rating	IP65	
Light Source	LED built in	
LED Type	SMD 2835	
LED Brand	Epistar	
LED Number	121	
F Mark	F	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	15,6-26W	
Power Factor	0,9	
Constant Current	Yes	
600mA	26-43,5V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Eaglerise	
Ilumination Data		
Colour Temperature	3000K	
Colour Temperature Lumen Output	3000K 1440lm	
Lumen Output	1440lm	
Lumen Output Light Efficiency	1440lm 60lm/W	
Lumen Output Light Efficiency CRI	1440lm 60lm/W	
Lumen Output Light Efficiency CRI	1440lm 60lm/W	
Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W	
Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W	
Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W 80	
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	1440lm 60lm/W 80 30,5cm	
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	1440lm 60lm/W 80 30,5cm 30,5cm	
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	1440lm 60lm/W 80 30,5cm 30,5cm 8,5cm	
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	1440lm 60lm/W 80 30,5cm 30,5cm 8,5cm 1.220kg	
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	1440lm 60lm/W 80 30,5cm 30,5cm 8,5cm 1.220kg	

Warranty	2 Years
Weee Directive	Yes



