# **Product Datasheet**

www.1-light.eu

### 14 Plafo>The LED Plafo Outdoor Round

## 67280N/AN/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











#### Downloads









#### Dimensions



#### **Physical Specification**

Item Group	14 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280N/AN/W
Colour	Anthracite
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	75mm
Diameter	260mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No	Pobrano z mamadecor.p
IK Rating	8	
atrical Charactaristics		
ctrical Characteristics		
Gear	Built In	
Fitting + Driver		
nput Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	16W	
IP Rating	IP65	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	500mA	
Voltage	30V	
Power(Watts)	15W	
IP Rating	IP65	
Light Source	LED built in	
LED Type	SMD 2835	
LED Brand	Epistar	
LED Number	81	
F Mark	F	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	8,5-16W	
Power Factor	0,9	
Constant Current	Yes	
500mA	19-32V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Eaglerise	
Ilumination Data		
Colour Temperature	3000K	
Colour Temperature  Lumen Output	3000K 960lm	
Lumen Output	960lm	
Lumen Output Light Efficiency	960lm 60lm/W	
Lumen Output Light Efficiency CRI	960lm 60lm/W	
Lumen Output  Light Efficiency  CRI  Illumination Diagram	960lm 60lm/W	
Lumen Output  Light Efficiency  CRI  Illumination Diagram	960lm 60lm/W	
Lumen Output  Light Efficiency  CRI  Illumination Diagram	960lm 60lm/W	
Lumen Output  Light Efficiency  CRI  Illumination Diagram	960lm 60lm/W 80	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	960lm 60lm/W 80 7	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	960lm 60lm/W 80 27cm 27cm	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	960lm 60lm/W 80 27cm 27cm 8cm	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	960lm 60lm/W 80 27cm 27cm 8cm 0.980kg	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight  Pcs/Carton	960lm 60lm/W 80 27cm 27cm 8cm 0.980kg 10	

Warranty	2 Years
Weee Directive	Yes



