Pobrano z mamadecor.pl

www.1-light.eu

Product Datasheet

Special Offers>Industrial & Floodlights

 \mathbf{P}

70106A/C



40W LED street light. High lumen output ideal for replacement of old HPS and mercury street lighting fittings.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
°O CE	303mm 0 60mm / 48mm 132mm 544mm

Physical Specification

Item Group	Special Offers
Family	Industrial & Floodlights
Order Code	70106A/C
Colour	Grey
Material	Die Cast
Shape	Rectangular
Length	644mm

Width	303mm
Height	132mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No



lectrical Characteristics	lectrical	Chara	cteristics
---------------------------	-----------	-------	------------

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constar
Input Current	500mA
Voltage	80V
Power(Watts)	40W
IP Rating	IP65
Light Source	LED bui
LED Type	СОВ
LED Brand	Cree
LED Number	24

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	40W



Power Factor	0,9 Pobrano z mamadecor.pl
Constant Current	Yes
500mA	80V
IP Rating	IP65
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector

Illumination Data

Colour Temperature	4000K
Lumen Output	3000lm
Light Efficiency	75lm/W
CRI	70
Beam Angle	140° x 70°
Illumination Diagram	

Packing Info

Box Weight	7Kg
Pcs/Carton	1
Barcode	5291889037880
HS Code	9405409900



Warranty	2 Years	Pobrano z mamadecor.pl
Weee Directive	Yes	

switch to one light!



