

## **Product Datasheet**

www.1-light.eu

### 21 Industrial & Floodlights>The Floodlights

7022/G/D



15x1W floodlight, IP65.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads





Dimensions



#### Gallery



#### Physical Specification

21 Industrial & Floodlights
The Floodlights
7022/G/D
Grey
Die Cast
Rectangular
230mm

Height	79mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15x1W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	200cm
F Mark	F
Fitting	
Input Type	Constant Current
Power(Watts)	15W
IP Rating	IP65
Gear	
Gear Type	Led Driver

220mm

Width

Pobrano z mamadecor.pl

Input Voltage	100-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	15W	
Power Factor	0,5	
Constant Current	Yes	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Eaglerise	
Protection	Short Circuit	
Ilumination Data		
Ilumination Data  Colour Temperature	6000K	
	6000K 1125lm	
Colour Temperature		
Colour Temperature  Lumen Output	1125lm	
Colour Temperature  Lumen Output  Light Efficiency	1125lm 75lm/W	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle	1125lm 75lm/W	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle	1125lm 75lm/W	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle  Illumination Diagram	1125lm 75lm/W 40°	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle  Illumination Diagram	1125lm 75lm/W	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle  Illumination Diagram	1125lm 75lm/W 40°	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle  Illumination Diagram	1125lm 75lm/VV 40° 2.943kg	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle  Illumination Diagram  Packing Info  Box Weight  Pcs/Carton	1125lm 75lm/VV 40° 2.943kg 4	
Colour Temperature  Lumen Output  Light Efficiency  Beam Angle  Illumination Diagram  Packing Info  Box Weight  Pcs/Carton  Barcode	1125lm 75lm/VV 40° 2.943kg 4 5291889016977	

#### Certification & Warranty

# switch to one light!

