

IKONPRO CCT

An addition to the popular IkonPRO recessed LED decking kit range, within each head there is a choice of colours. Featuring the unique design of removable and interchangeable heads, to change colour you simply turn the head 180° and reinsert into the loom. The Fresnel lenses improve lumen output, diffusing the spread of light evenly. Designed to be fitted and wired during the decking build stage without the heads, the supplied rubber caps protect the fitting from the elements until the decking is complete. Each individual IP67 head then simply plug in, adding the final touches to the decking design. Available in a variety of sizes and colours.

IKON PRO

IP67
RATED

EASY
INSTALL

A MEMBER OF
ACID
ANTI-CORROSION IN DESIGN

3000K/4000K



6500K/BLUE



- Constructed from stainless steel (304) & polycarbonate
- 10 x 0.75W LED module (SMD) CCT
- Min void: 80mm

CODE	DESCRIPTION	K	LM	LM/W	DIMENSIONS	CUT OUT
73347	IkonPRO CCT 25mm kit IP67	A	3000/4000	120	16	Proj: 1mm Dia: 25mm Dia: 20mm
73348	IkonPRO CCT 35mm kit IP67	A	3000/4000	280	37	Proj: 1mm Dia: 35mm Dia: 25mm
73349	IkonPRO CCT 45mm kit IP67	A	3000/4000	410	55	Proj: 1mm Dia: 45mm Dia: 32mm
76615	IkonPRO CCT 25mm kit IP67	A	6500/Blue	120	16	Proj: 1mm Dia: 25mm Dia: 20mm
76616	IkonPRO CCT 35mm kit IP67	A	6500/Blue	280	37	Proj: 1mm Dia: 35mm Dia: 25mm
76617	IkonPRO CCT 45mm kit IP67	A	6500/Blue	410	55	Proj: 1mm Dia: 45mm Dia: 32mm

Fitting the IkonPRO couldn't be easier....

The clever design of the IP67 connector means that you can mix the different colours and sizes too. Use the Ikon Pro heads to indicate a change of level or zone. The extension cable can be fitted between the driver and the first loom or between the two looms enabling you to configure your product perfectly.



IkonPRO inline sensors have been added to the range, PIR presence detectors and photocell twilight detector.



- Constructed from stainless steel (304) & polycarbonate

PIR PRESENCE DETECTOR

- 30 lux on, 30 lux off. 115 degree 1.5m detection range, 5 minutes ± 1min off after no movement

TWILIGHT DETECTOR

- 30 lux on, 30 lux off.

CODE	DESCRIPTION	DIMENSIONS	CUT OUT
71553	IkonPRO PIR presence detector IP67	Proj: 4mm Dia: 45mm	Dia: 32mm
71554	IkonPRO twilight detector IP67	Proj: 1mm Dia: 45mm	Dia: 32mm